



GASURVEYOR

3-500 / 6-500 / 11-500



The Gasurveyor 500 Series is GMI's most technologically advanced range of gas detectors to date.

FEATURES

- Flammable gas leak location instruments:
 - with mode for purging / inerting operations (3-500)
 - with Carbon Monoxide monitoring (6-500)
 - with Oxygen monitoring (11-500)
- Rechargeable or alkaline battery options.
- Approved to European and North American safety standards.
- Extremely robust anti-static case.
- Simple to use, 2-button operation.
- Built-in sampling pump as standard.
- Large LCD with automatic backlighting in low level light conditions.
- Audible / visual alarms for all gas ranges.
- Fault alarms for low flow, low battery etc.
- Compatible with the GMI range of Auto Calibration Systems.

Detection, Protection, Innovation



GMI. CONFIDENCE WHERE SAFETY IS CRITICAL. Gas Measurement Instruments designs, manufactures and markets a wide range of the highest quality proven personal portable and fixed gas monitoring systems. GMI is an international brand with a worldwide network of distributors and dedicated service centers ensuring fast and effective turnaround on instrument calibration and repair. Our uncompromising engineering excellence, established in over half a century of leadership, enables us to meet the exacting demands of industries where safety is critical. By building and maintaining strong relationships with our customers, GMI understands the unique challenges of the diverse markets we serve. Today, our proud heritage of pioneering gas leak monitors and detectors is shaping the future of GMI.



Gasurveyor 3-500 / 6-500 / 11-500

TECHNICAL SPECIFICATION			
Resolution:	LEL	0 to 10%	0.1%
		10% to 100%	1%
	VOL GAS	0 to 100%	1%
	Oxygen	0 to 25%	0.1%
	Carbon Monoxide	0 to 1000 PPM	1 PPM
Dimensions:	180 x 95 x 105 mm / 7.1 x 3.7 x 4.1in.		
Weight:	1.7 kg / 3.75 lbs		
Display:	LCD with automatic backlighting		
Humidity:	0-95% R.H. non-condensing		
Temperature:	-20°C to +50°C (-4°F to +122°F)		
Sampling:	Integral pump with flow fail sensor; sample path is protected by a hydrophobic filter and automatic pump switch-off		
Battery:	4 'D' size Alkaline Cells or Rechargeable Battery Pack		
Battery Life:	15 hours Alkaline or 9 hours Rechargeable		
Construction:	Moulded polypropylene case		
Rating:	IP54 (Dust protected and splashproof)		
Alarms:	Highly visible flashing LED Sounder: In excess of 80 db(A), typically 85 db(A) @ 1m		
Default Alarm Settings:	LEL - 20%		
	Oxygen - 19% Lo, 23% Hi		
	CO - 35 PPM		
Response Time (typical):	LEL Flammable: 3 secs (t_{50}); 5 secs (t_{90})		
	Oxygen: 7 secs (t_{90})		
	Toxics: 15 secs (t_{90})		
Certification:	ATEX  II 2 G EEx ia d IIC T4 (Ta = -20°C to +50°C)		
	IECEx Ex ia d IIC T4 (Ta = -20°C to +50°C)		
	 UL 913 Class I, Div 1 Groups A, B, C and D		
	 CSA Class I Groups ABCD C22.2 No. 152		



INSTRUMENT TYPE AND MEASURING RANGES	
Gasurveyor 3-500 (flammable gas only)	0 to 100% LEL 0 to 100% Volume Gas
Gasurveyor 6-500 (flammable gas and carbon monoxide)	0 to 100% LEL 0 to 100% Volume Gas 0 to 1000 PPM Carbon Monoxide
Gasurveyor 11-500 (flammable gas and oxygen)	0 to 100% LEL 0 to 100% Volume Gas 0 to 25% Oxygen

ORDERING INFORMATION	
42503	Gasurveyor 3-500 (Alkaline)
42503R	Gasurveyor 3-500 (Rechargeable)
42506	Gasurveyor 6-500 (Alkaline)
42506R	Gasurveyor 6-500 (Rechargeable)
42501	Gasurveyor 11-500 (Alkaline)
42501R	Gasurveyor 11-500 (Rechargeable)
	Above instruments are supplied with: Gasurveyor 500 Carrying Case; Shoulder Harness; 4mm Hex Driver; Standard Probe; Probe Handle Assembly; Sample Line Adaptor; Cotton Particulate Filters (Box of 10) x 2; User Handbook; 1m Clear Sample Line.
42151	Gasurveyor 500 Gas Industry Survey Accessory Pack Consisting of: Gas Industry Survey Carrying Case (Large); Probe Handle Assembly; Probe Handle Adaptor; Bellows Probe; Cotton Particulate Filters (Box of 10) x 2. Note: Large carrying case has space for special probes, e.g. Swan Neck
13184	Simple 'low cost' Charger c/w Universal Plug

For all sampling probes and accessories, and for calibration gases, contact GMI Ltd



Gas Measurement Instruments Ltd

GMI Headquarters

Inchinnan Business Park
Renfrew
PA4 9RG
Scotland
Tel: +44 (0) 141 812 3211
Fax: +44 (0) 141 812 7820
sales@gmiuk.com
www.gmiuk.com

Service and Calibration - UK

25 Cochran Close
Crownhill
Milton Keynes
MK8 0AJ
Tel: +44 (0) 1908 568 867
Fax: +44 (0) 1908 261 056
service@gmiuk.com
www.gmiuk.com

Service and Sales - USA

4055 Technology Forest Blvd.
The Woodlands, TX 77381
Tel: (713) 559-9290
Toll free: (877) 421-5315
Fax: (281) 292-2860
sales@detcon.com
www.detcon.com

Distributed by:

As an ISO 9001 approved company, Gas Measurement Instruments quality assurance programmes demand the continuous assessment and improvement of all GMI products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representative if you require more details.

© Copyright 2014 Gas Measurement Instruments Ltd

Gasurveyor 3 / 6 / 11-500 product brochure Part No. 99406

Issue 6 May 2015